

DISCONTINUED

2 Tools DME Station with Pneumatic Pump DMVE



Specifications

Selectable parameters

Selectable Temperature	90 to 450 °C / 190 to 840 °F
Dynamic Soldering Profiles	Designed to avoid thermal shock when soldering Ceramic Chip components like MLCC, this new and unique feature allows controlling the heating ramp up rate of the tool to gradually increase the temperature of the component through all the phases of the soldering process. Up to 25 fully configurable soldering profiles can be stored.

Special features

Sleep and Hibernation mode	These modes lower soldering tip temperature when the tool rests in the stand in order to avoid oxidation and extending tip life.
Max. and min. temperature	Limit the temperature range in which the operator is allowed to work.
Temperature levels	Instant selection of up to 3 editable temperature settings for solder joints with different heat requirement.
Soldering graphics	Real time visualization of tip temperature and power delivered to the solder joint during soldering process.
PIN protection	Keep station parameters protected against unauthorized access.
10 user interface languages	English, German, Spanish,

Product Packaging

Modular System	<u>DME</u> , <u>MVE-A</u>
Tools	<u>T245-A</u> , <u>DR560-A</u>
Stands	<u>AD-SE</u> , <u>DR-SE</u>
Cartridges	<u>C245903</u> , <u>C245906</u> , <u>C560003</u> , <u>C560004</u> , <u>C560005</u> , <u>C560013</u>
Cleaning Systems	<u>CL8499</u>

French, Italian, Portuguese,
Russian, Japanese, Korean,
Chinese.

Others	
Vacuum (at 6 bar)	90% / 680 mmHg / 26.8 inHg
Flow rate (at 6 bar)	15 SLPM
Air pressure supply	up to 6 bar
Connectivity	
USB-B (rear)	Software PC / Traceability
USB-A (front)	Firmware update.
	Soldering Graphics / Profiles management.
	Dino-Lite USB microscope connection. Compatible models: AM2011 and AM2111.
Robot	RS-232 remote control or Smart Fume Extractor connection
LAN	Remote control / Traceability
PS	Interconnection of up to 5 PSE control units to manage up to 24 tools simultaneously.
Equipotential bonding	
ESD/EOS	
ESD safe	
Tip to ground resistance	2 ohms
Tip to ground voltage	2 mV RMS
Power supply	
Peak power	160 W per tool – 23.5 V
Ambient operating temp.	10 to 40 °C / 50 to 104 °F
Dimensions and weight	
Control Unit	See individual modules
Package	368 x 474 x 195 mm / 10.62 kg
	14.5 x 18.7 x 7.7 in / 23.40 lb

Connectables

Modular System

Electric Desoldering Module for DDE & DME
MSE-A



Pneumatic Desoldering Module for DDE & DME
MVE-A



Nitrogen Flow Regulator for DDE, DME & HDE
MNE-A



Compatible tools

Micro Tweezers
PA120-A



Adjustable Micro Tweezers
AM120-A



Precision Purpose Handle
T210-A



Nitrogen Precision Handle
T210-NA



General Purpose Handle
T245-A



Nitrogen Handle
T245-NA



Thermal Tweezers
HT420-A



Micro Desoldering Iron
DS360-A



Desoldering Iron
DR560-A



Solder Feed Iron
AP250-A



Accessories

Nitrogen Kit for DDE & DME
KNE-A



Nitrogen Generator Module
GN-A



Cable collector
CC3702



Documentation

Manuals

DMVE-A Manual

Exploded View

Exploded View
Exploded View from series 181418
DMVE-A Exploded View from series 195375
DMVE-A Exploded View from serie 202671