

DISCONTINUED

Solder Feed station

CA-1E

This Station **comes with the Solder Feed Iron AP250** and works with **C250** Cartridges.

It suits for intensive soldering of THT components or for cable assemblies and is **very useful when a free hand is required.**

The Station comes with the JBC exclusive Heating System and the intelligent Sleep & Hibernation features.

Using the menu you can personalize **over 20 parametes.**

It incorporates a USB connector (type B) to update station software and create graphs.

A **complete Cleaning System** with antispash membrane and wiper with sponge is integrated.



Specifications

Net weight	2,86 kg (6.31lb)
Size	150x175x145 mm (0.59 x 0.67 x 5.71 in)
Voltage	230V / 120V / 100V
Input fuse	1A (230V), 2A (120V and 100V)
Output peak power	130W / 23.5V
Temperature selection	90-450 °C / 190-840 °F
Tip to ground resistance	2 ohms
Tip to ground voltage	2mV RMS
Ambient operating temp.	10-40 °C / 50-104 °F
ESD safe	
Solder Wire Diameter	0.8-1.5 mm (0.03-0.06 in)
USB interface station-PC	
Package weight	3,28 kg (7.23lb)
Package dimensions	2344 x 234 x 258 mm (92.28 x 9.21 x 10.16 in)

Connectables

Product Packaging

Modular System	CA with tip cleaning system
Tools	<u>AP250-A</u>
Cartridges	<u>C250403</u>
Consumables	<u>S0354</u> , <u>CL0160</u> , <u>CL6210</u>

Connectables

Compatible tools

Solder Feed Iron
AP250-A



Accessories

Cable collector
CC3702



Documentation

VideoTutorial	AP250 tutorial
VideoTutorial	Adjustable Elements CD
Manuals	CA-E Manual
Exploded View	CA-E Exploded View