

Auto Feed Iron

SF250-A

The SF250 is appropriate for **extensive soldering** applications that require **one free hand**.

Using the Push Button, the **solder wire** will be **automatically provided**.

This Auto Feed Iron suits to feed **perforated solder wire**. This means better flux flow and outgassing, avoids solder and flux splashing.

It incorporates an **anti-rotation screw** for best **cartridge alignment**.

The Auto Feed Iron is **connectable** to an **Automatic Solder Feeder SE** and at the same time to a **Modular Station** by means of the **Stand SF250-SE** (sold separately).

It works with C250 cartridges and is supplied with the C250403 Cartridge and the Guide Set (0022295) for **Solder Wire Ø 0.9 - 1.0 mm**.



Specifications

Net weight	0,20 kg (0.45lb)
Package weight	0,40 kg (0.88lb)
Package dimensions	300 x 125 x 65 mm (11.81 x 4.92 x 2.56 in)

ESD safe

Connectables

Modular System

1 Tool Control Unit
DI



2 Tools Control Unit
DDE



4 Tools Control Unit
DME



Connectables

Accessories

Solder Feeder 230 V & Ø 1 mm
SF-210VB



Solder Feeder 100-120 V & Ø 1 mm
SF-110VB



Documentation

Manuals SF250-A Manual

Exploded View EXPLODED SF250-A