

# Desoldering Iron

## DR560-A

DR is an iron for desoldering jobs of through-hole components and removing excess solder after SMD rework. It is capable of providing up to 160W.

The exclusive JBC heating system and the suction power from MSE or MVE pumps ensure the optimum quality.

When the solder container is made of glass you can see when it needs cleaning and the filters need replacing.

DR uses C560 cartridges with internal diameters of 0.6 - 3 mm. Some tips are specially designed for cleaning traces of tin from PADS.

The desoldering iron comes with the C560003 tip.  
Also supplied with C560013, C560004, C560005 and accessories.



### Specifications

Net weight	0,41 kg (0.91lb)
ESD safe	
Package weight	559 gr (1.23 lb)
Package dimensions	300 x 125 x 65 mm (11.81 x 4.92 x 2.56 in)
	413 gr (0.91 lb)

### Product Packaging

Tools	<u>DR560-A</u>
Cartridges	<u>C560003</u> , <u>C560004</u> , <u>C560005</u> , <u>C560013</u>

### Connectables

#### Modular System

1 Tool Control Unit  
DI



2 Tools Control Unit  
DDE



4 Tools Control Unit  
DME



Electric Desoldering Module for  
DI  
MS-A



Electric Desoldering Module for  
DDE & DME  
MSE-A



Pneumatic Desoldering Module  
for DI  
MV-A



Pneumatic Desoldering Module  
for DDE & DME  
MVE-A



## Connectables

### Stands

Stand for DR560  
DR-SE



### Consumables

Heating element DR560-A  
DSV-DR



## Documentation

VideoTutorial	DR560-A main features
VideoTutorial	Changing the DSV-DR Heating element
VideoTutorial	How to change the DR560 Glass Solder Collector?
Manuals	DR560-A Manual
Exploded View	DR560 Exploded View