

C360 Tips

Micro Desoldering Tips for DS360

This manual corresponds to the following references:

Through Hole Desoldering

- Ref. C36001 (Ø 0.6)
- Ref. C36002 (Ø 0.8)
- Ref. **C36003** (Ø 1.0)
- Ref. C36004 (Ø 1.2)
- Ref. C36007 (Ø 1.4)
- Ref. C36006 (Ø 3.0)

Pad Cleaning

- Ref. C36011 (Ø 0.6)
- Ref. C36012 (Ø 0.8)
- Ref. C36013 (Ø 1.0)
- Ref. C36014 (Ø 1.2)

Packing list



C360 Tips 10 units According to purchased reference



Manual 1 unit Ref. **0007419**


Tip care

The largest rod that fits in the tip hole should periodically be passed through in order to clean the intake tube.

The microdesoldering tips are protected against oxidization and wear.

Do not use abrasive tools which may damage the tips protective surface coating and avoid knocking them about.


To maintain the tips, use the recommended cleaning methods (brass wool, brushes, sponge). Only use the TT-A re-tinner when absolutely necessary.





C360 Tip Ranges

		Ø A		ØB		Ø max. pin	
	Ref.	mm	in	mm	in	mm	in
Through hole desoldering	C36001	1.0	0.039	0.6	0.024	0.4	0.016
	C36002	1.2	0.047	0.8	0.032	0.6	0.024
	C36003	1.4	0.055	1.0	0.039	0.8	0.032
	C36004	1.6	0.063	1.2	0.047	1.0	0.039
	C36007	1.9	0.075	1.4	0.055	1.2	0.047
	C36006	3.0	0.118	1.5	0.059	1.3	0.051
Pad cleaning	C36011	1.0	0.039	0.6	0.024	-	-
	C36012	1.3	0.051	0.8	0.032	-	-
	C36013	1.4	0.055	1.0	0.039	-	-
	C36014	1.6	0.063	1.2	0.047	-	-





Warranty

JBC's 2 year warranty covers this equipment against all manufacturing defects, including the replacement of defective parts and labour.

Warranty does not cover product wear or misuse.

In order for the warranty to be valid, equipment must be returned, postage paid, to the dealer where it was purchased.



This product should not be thrown in the garbage. In accordance with the European directive 2012/19/EU, electronic equipment at the end of its life must be collected and returned to an authorized recycling facility.









www.jbctools.com